

## ENGINEERING DATA SHEET

**2475**

(Packaged and Configured)

CCN: 47725347  
 Rev: B ECO 1434180  
 Page: 1 of 3  
 Date: 28-Jan-21

**Point of Manufacture - Campbellville****Bare Details:**

## Specifications:

Bore: 4" & 2.5"  
 Stroke: 2.75"  
 Maximum pressure : 250(17.24) psig(bar)  
 Sheave OD: 13.75"  
 Sheave PD: 13.5"  
 Inlet size: 1" NPT  
 Discharge size: 0.5" NPT  
 Belt Type / Quantity: A/1  
 Min/Max RPM: 575/1600  
 Air-cooled Aftercooler CTD: 25°F

## Lubrication:

Types: \*XL300; \*\*All-Season T30 Select; \*\*\*XL740Ht  
 Sump capacity: 1.30(1.23) qt(liter)

\*Adjust viscosity to suit ambient conditions, XL300 should not be used in ambients below 40°F.  
 Use premium quality, non-detergent, single-viscosity petroleum oils with R & O additives.

\*\* Required for duty cycles above 70% load. Check lubricant compatibility sheet before using.

\*\*\* Required for ambients in excess of 100°F. Check lubricant compatibility sheet before using.

**Tank Details:**

Tank size / Configuration: 30 Gal/Horizontal (Gas / Diesel Only)  
 80 Gal/Vertical  
 80 Gal/Horizontal  
 120 Gal/Horizontal (Duplex Only)

Pressure rating: 200(13.8) psig(bar)  
 Codes: ASME Sec VIII & CRN

**PORTLAND  
 COMPRESSOR**  
*Experience You Can Depend On*  
 800-542-8300

**Drive Details:****AMP draw:**

	200-1-60	230-1-60	200-3-60	230-3-60	460-3-60	575-3-60
5HP	32.2	28	17.5	15.2	7.6	6.1
7.5HP		40	25.3	22.0	11	9.0

**Note:** Nominal Amps are based on NEC full load amperage rating for this size motor. Actual nameplate amps may vary according to motor design and/or motor manufacturer. Duplexes have the potential to run both motors at the same time, in this instance double the amp draw value.

	5 HP	7.5 HP	7.5 HP	13 HP	14 HP	9.3 HP
Configured = C)	P;C	P;C	P;C	P	P	P
<b>Efficiency</b>	*	*	*	N/A	N/A	N/A
<b>Motor RPM</b>	1775	3450	1775	3600	3600	3600

\* Motors comply with EISA standards.

**2475**

CCN: 47725347

Page: 2 of 3

**Performance Data:**

Bare	Power (HP)	Pressure	Pump	Flow	BHP
2475 (P;C)	5	75	1040	17.3	4.5
2475 (P;C)	5	125	1040	17.1	4.8
2475 (P;C)	5	175	1040	16.8	5.5
H2475 (C)	5	250	910	14.1	5.2
2475 (P;C)	7.5	75	1500	24.3	7.3
2475 (P;C)	7.5	125	1500	24.2	7.8
2475 (P;C)	7.5	175	1500	24.0	8.1
2475 - Gas-Honda (P)	13	175	1600	25.0	8.2
2475 - Gas-Kohler (P)	14	175	1600	25.0	8.2
2475 - Diesel-Yanmar (P)	9.3	175	1415	22.6	7.6
2475 - Diesel-Kohler (P)	8.5	175	1375	22.0	7.4

**Note:** Duplex units multiply capacity by two when both units are running.

**Operating Environment:**

Minimum operating temperature: 32(0) deg.F(deg.C)

Maximum operating temperature: 100(37.78) deg.F(deg.C)

**Electricals:**

Magnetic starter:

Pressure switch:

Alternator:

	Fully Packaged	Configured
Magnetic starter:	E-Series standard	E-Series standard; Deluxe optional
Pressure switch:	Non-adjustable standard	Non-adjustable standard; Adjustable
Alternator:	E-Series standard	E-Series standard; Deluxe optional

**Dimensions & Shipping weight:**

	5 HP 80 Gal. Vertical	5 HP 80 Gal. Horizontal	5 HP (Duplex) 120 Gal. Horizontal
L x W x H (in):	48 x 40 x 76	74 x 43 x 49	88 x 60 x 60
Weight (lbs):	670	500	1300

	7.5 HP 80 Gal. Vertical	7.5 HP 80 Gal. Horizontal	7.5 HP (Duplex) 120 Gal. Horizontal
L x W x H (in):	48 x 40 x 76	74 x 43 x 49	88 x 60 x 60
Weight (lbs):	675	525	1350

	Gas Engine Driven 30 Gal. Horizontal	Diesel Engine Driven 30 Gal. Horizontal	Gas Engine Driven Baseplate
L x W x H (in):	48 x 22 x 41	48 x 22 x 45	48 x 27 x 22
Weight (lbs):	455	515	390

**Note:** For model specific dimensions and weight, reference GA drawings.

PORTLAND  
COMPRESSOR

Experience You Can Depend On  
800-542-8300

2475



CCN: 47725347

Page: 3 of 3

- 
- Notes:**
- 1) For specific code requirements like CSA, CRN, ASME contact your channel marketing manager.
  - 2) For model specific GA, electrical schematic and fluid flow schematic or any specific information contact your channel marketing manager.

**SPECIAL OPTIONS/FEATURES NOT AVAILABLE ON THESE UNITS**

**PORTLAND  
COMPRESSOR**  
*Experience You Can Depend On*  
**800-542-8300**